



WASHING

PRODUCTS » ALP SERIES » WARE WASHERS



## ALP 43

SOFT-TOUCH PROGRAMMABLE WARE WASHERS

Stainless steel structure 18/10 AISI 304. Double-skinned balanced dual door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Washing system having 3 wash arms in the lower part and a rotating wash arm in the upper part with particularly shaped jets for keeping them free from solid waste.

**Three working cycles:** 120 seconds, 240 seconds or continuous.

High capacity **double-boiler system.**

Double stainless steel surface filters in the tank for collecting solid waste.

Low tension (24V) **soft-touch** control panel. Temperature thermometer.

Possibility to change the cycle parameters thanks to palmtop with simple logic. Possibility to program the working cycle.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85° C: the ideal temperature for strongly reducing the bacterial load.

Steam is carried out through a chimney.

Rack: 570 x 570 mm. Possibility to wash baking trays and other items **up to 600 mm.**

**Standard equipped** with a built-in rinse aid dispenser for the best drying results.

**Standard equipped** with a built-in connection for detergent dispenser.

Wide range of options available **on demand.**

A special concave door suitable for washing a basket 600 x 400 mm available **on demand.**

**Standard equipped** with a stainless steel rack and a rack for ladles.

© 2011

ATA Srl  
V.le del Progresso, 20  
Z.I. 35026 CONSELVE (PD)  
ITALY

TEL: (+39) 049 95 00 555  
FAX: (+39) 049 95 00 560

P.I. e C.F. 01897630289  
Reg.Imp. PD N. 01897630289

### TECHNICAL SPECIFICATIONS

Width: 685 mm

Depth: 750 mm

Height: 1720 mm

Volume: 0.88 m<sup>3</sup>

Rack dimensions: 570x570 mm

Useful height: 640 mm

Working cycles: 120-240 + ∞

El. power consumption: 9 kW

El. power: 230 V / 3 – 400 V / 3+N/ 50-60 Hz

Racks/Hour: 30/ 15