

ALP01GS

SOFT-TOUCH PROGRAMMABLE WARE WASHERS - RACK 600 x 700 mm



PRODUCT DESCRIPTION

Stainless steel structure 18/10 AISI 304. Double-skinned balanced dual door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Washing system having 3 wash arms in the upper part and 4 wash arms in the lower part with particularly shaped jets for keeping them free from solid waste.

Three working cycles: 120 seconds, 240 seconds or continuous.

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank for collecting solid waste.

Low tension (24V) **soft-touch** control panel. Temperature thermometer.

Possibility to change the cycle parameters thanks to palmtop with simple logic. Possibility to program the working cycle.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

Steam is carried out through a chimney.

The built-in **W.A.G.P.** system ensures excellent rinsing and prevents dirty water from flowing back to the main water system. 600 x 700 mm basket. Possibility to wash baking trays and other items **up to 600 mm**.

The lower wash pump is more powerful than the upper wash pump and it has a delayed action, so that items to wash do not move from their position when the washing cycle starts.

Standard equipped with built-in rinse aid dispenser for the best drying results. Standard equipped with built-in connection for detergent dispenser.

Wide range of options available on demand. Winding shower available on demand.

Standard equipped with a stainless steel plain rack, a rack for baking trays and a ladles rack.







TECHNICAL SPECIFICATIONS

Width: 800 mm Depth: 860 mm Height: 1900 mm Volume: 1.31 m³ Rack dimensions: 600x700 mm Useful height: 640 Working cycles: 120-240 + inf. sec Electrical power: 12.70 kW Electric power: 230 V/ 3 - 400 V / 3+N/ 50-60 Hz Racks/Hour: 30-15 WAGP: Standard



